



CUSHMAN®

SHUTTLE™ 4



MOVE PEOPLE AND GEAR WITH EASE.

If you need a general-purpose vehicle to move around your facility, look no further than the Cushman® Shuttle™ 4. It combines four forward-facing seats with a spacious cargo bed for efficient transport of personnel and equipment. Available in both a 48V electric model and a gas-powered option with a 13.5 hp Kawasaki® engine, the Shuttle 4 keep passengers and their gear comfortable on the move.

LET'S WORK.®

13.5HP
KAWASAKI®
GAS ENGINE
OPTION

48V
ELECTRIC
DRIVETRAIN
OPTION

1200LB
TOTAL LOAD
CAPACITY



CUSHMAN® SHUTTLE™ 4



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rear View Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pin Stripes
- Body Color (Forest Green, White or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

GAS MODEL

| BODY & CHASSIS | |
|--------------------------|---|
| FRAME | Welded Steel w/ DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear) |
| STANDARD COLOR | Patriot Blue |
| DIMENSIONS | |
| OVERALL LENGTH | 135.0 in (343 cm) |
| OVERALL WIDTH | 48.5 in (123 cm) |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) |
| WHEEL BASE | 93.5 in (237 cm) |
| WHEEL TRACK | 34.2 in (87 cm) Front / 38.0 in (97 cm) Rear |
| GROUND CLEARANCE | 4.3 in (11 cm) |
| CARGO DECK CAPACITY | 9 cu ft (.25 m³) |
| CARGO DECK MATERIAL | Wood Stake Sides |
| POWER | |
| POWER SOURCE | 48V DC |
| VALVE TRAIN | N/A |
| HORSEPOWER (KW) | 18.1 hp (13.5 kW) Intermittent |
| ELECTRICAL SYSTEM | 48V |
| BATTERY (QTY/TYPE) | Eight, 6V Deep Cycle |
| BATTERY CHARGER | 48 VDC Delta Q, 120/230V AC, UL & CSA |
| KEY OR PEDAL START | Pedal |
| AIR CLEANER | N/A |
| LUBRICATION | N/A |
| OIL FILTER | N/A |
| COOLING SYSTEM | N/A |
| FUEL CAPACITY | N/A |
| SPEED CONTROLLER | 400 Amp Precision Drive System (PDS) |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential w/ Helical Gears |
| GEAR SELECTION | Dash-Mounted Forward-Neutral-Reverse |
| REAR AXLE RATIO | 14.7:1 |
| PERFORMANCE | |
| SEATING CAPACITY | 4-Person |
| WEIGHT W/O BATTERIES | 720 lb (327 kg) |
| CURB WEIGHT | 1200 lb (544 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) |
| BED LOAD CAPACITY | 400 lb (181 kg) |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) |
| SPEED | 13 mph ± 0.5 mph (21 kph ± 0.8kph) |
| STEERING & SUSPENSION | |
| STEERING | Self-Compensating Rack & Pinion |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical, Self-Adjusting Drum |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | Links 18 x 8.5 - 8 (4 Ply Rated) |

www.cushman.com

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82283-G4 (Rev. 01/2016)